

UBK series clamping frame for shielding conductors

Structure

Including frame, clamping plate and spring. The material is cold rolled steel sheet, and 65Mn spring steel wire, with Ni plating, compact and practical.

Usage

It can connect all kinds of cable shielding (eg, snap on 10×3mm pure copper busbar with clamping plate, work together with mainwire stand (installed on TH35-7.5 rail, work with terminal blocks) to ensure the system more professional and reasonable.

Model and indications



Models

Model	UBK 2X2-6	UBK 3-6	UBK 4-13.5	UBK 10-20	UBK 15-32
Outer diameter range of shielding conductor	2-6mm	3-6mm	4-13.5mm	10-20mm	15-32mm
Order No.	401001	401002	401003	401004	401005



Notes:

1. Snap UBK on 3×10 busbar or cable shielding layer by hands directly.
2. Do not need other tools.
3. The spring which in clamping frame with strong flexibility, can connect large range conductor.
4. Installed the mainwire stand on TH35-7.5 mounting rail, work with terminal blocks.

Models**Mainwire stand
UPS-125M/1P****Mainwire stand
UPS-125M/2P****Mainwire stand
UPS-125M/3P****Mainwire stand
UPS-125M/3 + 1P**

Dimensions Width/thickness/height	24.6/24/24	46/10/51	70/10/58	
Rated voltage	380V	380V	380V	380V
Phase	1	2	3	4
Quantity(pack)	2	2	2	2
Busbar conductor				
Models	3x10 3x10 + 3x6	3x10 3x10 + 3x6	3x10 3x10 + 3x6	3x10 3x10 + 3x6