

Gama de disipadores de calor

Sufijo	Referencia	Foto	Rthsa especificada para un valor concreto en W	Dimensiones An x Al x P (mm)	Montaje	Cantidad máxima de relés estáticos por disipador				
						RA.. RD.. RM1.. RAM1.. RS1..	RGS1..	RGS1S..E	RGS1S..U	RR2.. RZ3..
H8	RHS00		12.3 °C/W (>10W)	44 x 82 x 16	DIN	1	-	-	-	-
H1	RHS300		5.40 °C/W (>30W)	105 x 82 x 20	DIN	-	-	-	-	1
H51	RHS37A		4.00 °C/W (>20W)	18 x 110 x 52	DIN	-	1	1	-	-
H47	RHS10015		4.00 °C/W (>30W)	100 x 82 x 29	DIN	2	-	-	-	-
H60	RHS5050D		3.50 °C/W (>25W)	80 x 50 x 51	Panel	1	-	-	-	-
H0	RHS100 RHS100D		3.10 °C/W (>25W)	44 x 82 x 48	DIN	1	-	-	-	-
H53	RHS38AD		2.85 °C/W (>40W)	46 x 76 x 33	Panel	1	-	-	-	-
H15	RHS45C RHS45CD		2.20 °C/W (>45W)	45 x 103 x 55	DIN DIN	1	-	-	-	-
H61	RHS52A		2.00 °C/W (>45W)	22.5 x 110 x 90	DIN	-	1	1	-	-
H5	RHS45B RHS45BD		1.85 °C/W (>50W)	45 x 103 x 80	DIN	1	-	-	-	-
H49	RHS10025D		1.85 °C/W (>60W)	100 x 100 x 25	Pared, Panel	1	3	2	1	-
H65	RHS540 RHS540D		1.85 °C/W (>60W)	54 x 110 x 51	DIN	1 1	3 3	1 1	1 1	- -
H66	RHS542 RHS542D		1.85 °C/W (>60W)	54 x 110 x 51	DIN	- -	2 2	2 2	- -	- -
H48	RHS5840D		1.80 °C/W (>60W)	81 x 100 x 40	Panel	1	3	2	1	-
H58	RHS10067D		1.70 °C/W (>20W)	121 x 76 x 67	Panel	1	-	-	-	-
H55	RHS16225D		1.30 °C/W (>90W)	162 x 100 x 25	Pared, Panel	3	3	3	3	1
H75	RHS703 RHS703D		1.10 °C/W (>60W)	72 x 110 x 75	DIN	1	3	2	2	-
H16	RHS90A RHS90AD		0.97 °C/W (>60W)	90 x 103 x 80	DIN	1	-	-	-	-
H58L	RHS10067LD		0.88 °C/W (>80W)	121 x 140 x 67	Panel	2	2	-	-	-
H55L	RHS16225LD		0.84 °C/W (>120W)	162 x 250 x 25	Pared, Panel	3	3	3	3	1
H2	RHS301 RHS301D		0.82 °C/W (>80W)	119 x 82 x 94	DIN	2	-	-	-	1
H17	RHS112A RHS112AD		0.76 °C/W (>100W)	112 x 103 x 80	DIN	2	-	-	-	1
H67	RHS540F40-24		0.65 °C/W	54 x 135 x 51	DIN	1	3	1	1	-
H68	RHS542F40-24		0.65 °C/W	54 x 135 x 51	DIN	-	2	2	-	-
H78	RHS11267D		0.54 °C/W (>150W)	112 x 125 x 67	Panel	1	3	2	2	-
H78D	RHS11267DIND		0.54 °C/W (>150W)	119 x 125 x 94	DIN	2	3	3	2	1
H13	RHS320		0.40 °C/W (>120W)	240 x 100 x 93	Panel	3	3	3	3	1
H57	RHS30040D		0.40 °C/W (>180W)	300 x 200 x 40	Pared	8	12	12	5	-
H76	RHS703F60-24		0.37 °C/W	72 x 141 x 75	DIN	1	3	2	2	-
H77	RHS703F60-230		0.37 °C/W	72 x 141 x 75	DIN	1	3	2	2	-
H18	RHS112AF60-24		0.35 °C/W	112 x 120 x 80	DIN	2	1	-	-	-
H52	RHS112AF60-230		0.35 °C/W	112 x 120 x 80	DIN	2	1	-	-	-
H10	RHS301F115C		0.28 °C/W	124 x 146 x 122	DIN	2	1	-	-	-
H12	RHS301F230C		0.28 °C/W	124 x 146 x 122	DIN	2	1	-	-	-
H41	RHS28009F80-24P		0.12 °C/W	280 x 87 x 122	DIN	4	9	9	4	-
H44	RHS28011F80-24P		0.12 °C/W	280 x 87 x 122	DIN	3	11	6	5	-



HERRAMIENTA ON-LINE PARA LA SELECCIÓN DEL DISIPADOR MÁS ADECUADO

Accede a través del siguiente link: <http://bit.ly/1OpPCdr>